

PRODUCT SPECIFICATIONS

PASSENGER CAR, LIGHT TRUCK ENGINE & TRANSMISSION FILTRATION



ATF-09 FILTER HOUSING / C-09 FILTER CARTRIDGE

FILTER HOUSING

Filter Efficiency: Beta (B) 4=10649
Oil Volume Engine: Appr. 5 liter / 5.28 quarts
Oil Volume Transmission: Appr. 18 liter / 19 quarts
Dimensions: Ø 94 x 135 mm / 3.70 x 5.31 inches
Material: Aluminum
Weight: 0.7 kg / 1.54 pounds
Volume: 0.28 liter / 0.29 quarts
Inlet: M10 x 1
Outlet: M10 x 1
Max. Pressure: 7 Bar / 102.9 psi
Max. Operating: 140°C / 284°F
Part Number: 01-ATF-09

FILTER CARTRIDGE

Material: Long Fibre Cellulose
Dimensions: Ø 53 x 90 mm / 2.08 x 3.54 inches
Weight: 50 g / 1.76 oz.
Flow Direction: Radial
Filter Surface Area: 150 cm² / 23.25 cu. inch
Retention Value (Nominal): 0.5 micron
Total Liquid Absorption: 30 ml / 1.01 fluid oz. H₂O
Flow Rate (Nominal): 1.5 liter / 1.58 quarts / min.
Filter Cartridge Part Number 02-C-09B



TransProtector™ INLINE MAGNETIC FILTER

Outer Construction: 409 Stainless Steel
Joints: Laser Weld
Media: NTZ MicroClean Element
Inlet Sizes: 5/16", 3/8" or 1/2"
Flow: Delta P @ 1.0 GPM / 1.0 psid
Bypass Valve: Nominal Release 7 psid
Safety: Filtering Reverse Flow Safety Mode
Installed Inline
Part Number: TP516 AC (inlet size 5/16")
TP038 (inlet size 3/8")
TP012 (inlet size 1/2")

EP NTZ Micro Filtration, LLC

The smart choice.

2424 John Daly
Inkster, Michigan 48141 USA
1.313.750.1740
1.866.PUR.DEL.1
www.epntz-filters.com